



RULEXX PLUS SAE 0W40 API SP

DESCRIPTION:

Rulexx Plus SAE 0W-40 API SP is a premium, fully synthetic engine oil designed for modern gasoline engines, offering excellent fuel efficiency and engine protection. It is a high reach quality lubricant, completely manufactured, uniquely figured out to meet the most recent execution prerequisites of present day motors.

APPLICATION:

This product meets or exceeds the requirements of the latest API and ILSAC industry specifications for petrol and hybrid engine oils, as well as the requirements of many major American engine manufacturers. Suitable for use in passenger cars.

SPECIFICATIONS:

Rulexx Plus SAE 0W-40 API SP fully synthetic motor oil meets the requirements of all major car manufacturers and the following standards:

ILSAC GF-6; ACEA A5/B5; Chrysler 6395; GM 6094M, 4718M; Porsche "C40"
Ford WSS M2C946-A, M2C929-A; Honda HTO-06, BMW: Long Life LL-01, LL-04;
Mercedes Benz – sheet 229.71, 229.72; VW 505.00/502.00

BENEFITS:

- Enhanced protection against sludge, oxidation, and wear, making it ideal for turbocharged and gasoline direct-injection engines.
- It also reduces emissions, helping to maintain clean engines, ensuring longer engine life and superior overall performance.
- Reduces chlorine content to meet the environmental requirements.
- Custom designed which helps to meet manufacturer's requirement to extend interval between oil changes.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT SAE 0W40 SP
Appearance	Visual	Bright & Clear
Color	ASTM D 1500	Neutral
Viscosity @40°C	ASTM D 44	72.09
Viscosity @100°C	ASTM D 445	14.12 cSt
Viscosity Index	ASTM D 2270	204.8
Density @15°C	ASTM D 1298	0.8441
Pour Point	ASTM 97	-43°C
Flash point	ASTM D 92	228°C
TBN	ASTM D 6304	8.6