



RULEXX PLUS SAE 0W20 API SN

DESCRIPTION:

Rulexx Plus SAE 0W-20 API SP is a high-performance, low-viscosity engine oil designed for modern vehicles, providing excellent fuel efficiency and engine protection. The “0W” indicates superior cold-start protection, allowing the oil to flow quickly even in extremely low temperatures. The “20” ensures optimal lubrication at high operating temperatures.

APPLICATION:

This product meets or exceeds the requirements of the latest API and ILSAC industry specifications for petrol and hybrid engine oils, as well as the requirements of many major American engine manufacturers. Suitable for use in passenger cars.

SPECIFICATIONS:

Rulexx Plus SAE 0W-20 API SP full synthetic motor oil meets the requirements of all major car manufacturers and the following standards:

ILSAC GF-6; ACEA A5/B5; Chrysler 6395; GM 6094M, 4718M; Porsche "C20" ;
Ford WSS M2C946-A, M2C929-A; Honda HTO-06, BMW: Long Life LL17FE,
Mercedes Benz – sheet 229.71, 229.72, VW 508.00/509.00.

BENEFITS:

- Enhanced protection against sludge, oxidation, and wear, making it ideal for turbocharged and gasoline direct-injection engines.
- It also reduces emissions, helping to maintain clean engines, ensuring longer engine life and superior overall performance.
- Reduces chlorine content to meet the environmental requirements.
- Custom designed which helps to meet manufacturer's requirement to extend interval between oil changes.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT SAE 0W20 SP
Appearance	Visual	Bright & Clear
Color	ASTM D 1500	Neutral
Viscosity @40°C	ASTM D 44	43.19
Viscosity @100°C	ASTM D 445	8.34 cSt
Viscosity Index	ASTM D 2270	172
Density @15°C	ASTM D 1298	0.8449
Pour Point	ASTM 97	-40°C
Flash point	ASTM D 92	224°C
TBN	ASTM D 6304	8.6