



RULEXX PLUS SAE 10W40 API SN

DESCRIPTION:

Rulexx Plus SAE 10W40 API SN is a synthetic technology engine oil developed for the most recent requirement of gasoline passenger engines. It meets all current industry standard requirements of domestic car makers recommending API SN. It is formulated from premium quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions.

APPLICATION:

10W40 SN can be used under the most difficult operating conditions (highways, congested city traffic, etc.) for every season. Recommended for all petrol engines (multi-valve and turbo types) turbo-charged or naturally aspirated in cars.

SPECIFICATIONS:

Rulexx Plus SAE 10W-40 API SN full synthetic motor oil meets the requirements of all major car manufacturers and the following standards:

ILSAC GF-5; ACEA A3/B4; BMW Long Life LL-01, LL-04; MB 229.51, MB 229.52.

PSAB71 2296, RENAULT RN0700/ RN0710; VW 505.00/502.00, Porsche A40;

CHRYSLER MS-12991, FIAT 9.55535-H2/M2/N2/Z2.

BENEFITS:

- Excellent engine protection by providing outstanding protection against corrosive & abrasive wear.
- Protects against start-up wear in cold conditions through excellent low-temperature fluidity.
- Maintains power and economy by minimizing wear.
- Improved shear stability maintains viscosity in-grade under severe, high-temperature service conditions.
- Excellent low-temperature pumpability ensures smooth cold starting and improved fuel economy.
- Engine Cleanliness and low combustion residue.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	Visual	Bright & Clear
Color	ASTM D 1500	Neutral
Viscosity @40°C	ASTM D 44	REPORT
Viscosity @100°C	ASTM D445	12.5-16.3 cSt
Viscosity Index	ASTM D 2270	130
Density @15°C	ASTM D 1298	0.855
Pour Point	ASTM 97	-32°C
Flash point	ASTM D 92	225°C