



RULEXX PLUS SAE 5W40 API SP

DESCRIPTION:

Rulexx Plus SAE 5W-40 API SP is a premium, fully synthetic engine oil designed for modern gasoline engines, offering excellent fuel efficiency and engine protection. It is a high reach quality lubricant, completely manufactured, uniquely figured out to meet the most recent execution prerequisites of present day motors.

APPLICATION:

This product meets or exceeds the requirements of the latest API and ACEA industry specifications for petrol engine oils, as well as the requirements of many major American, and European engine manufacturers. Suitable for use in both gasoline and hybrid passenger cars and light commercial vehicles.

SPECIFICATIONS:

Rulexx Plus SAE 5W-40 API SP full synthetic motor oil meets the requirements of all major car manufacturers and the following standards:

ILSAC GF-5; ACEA A3/B4; BMW Long Life LL-01, LL-04; MB 229.51, MB 229.52.

PSAB71 2296, RENAULT RN0700/ RN0710; VW 505.00/502.00, Porsche A40;

CHRYSLER MS-12991, FIAT 9.55535-H2/M2/N2/Z2.

BENEFITS:

- Its special and exclusive formula helps your vehicle maintain maximum horsepower by reducing sludge formation.
- Excellent performance for the higher power and speeds in modern engines.
Enhances life of crankcase.
- The outstanding thermal stability and resistance to oxidation of this oil prevent any degradation, even in extreme usage conditions which helps to extend engine life.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	Visual	Bright & Clear
Color	ASTM D 1500	Neutral
Viscosity @40°C	ASTM D 44	89.30
Viscosity @100°C	ASTM D445	14.49 cSt
Viscosity Index	ASTM D 2270	169.0
Density @15°C	ASTM D 1298	0.8550
Pour Point	ASTM 97	-36°C
Flash point	ASTM D 92	223°C
TBN	ASTM D 6304	7.8