



RULEXX PLUS SAE 5W30 API SP

DESCRIPTION:

Rulexx Plus SAE 5W-30 API SP is a premium, fully synthetic engine oil designed for modern gasoline engines, offering excellent fuel efficiency and engine protection. It is a high reach quality lubricant, completely manufactured, uniquely figured out to meet the most recent execution prerequisites of present day motors.

APPLICATION:

This product meets or exceeds the requirements of the latest API and ACEA industry specifications for petrol engine oils, as well as the requirements of many major American, and European engine manufacturers. Suitable for use in both gasoline and hybrid passenger cars and light commercial vehicles.

SPECIFICATIONS:

Rulexx Plus SAE 5W-30 API SP full synthetic motor oil meets the requirements of all major car manufacturers and the following standards:

ILSAC GF-5; ACEA C3/C2; BMW Long Life-04; MB 229.31, MB 229.51, MB 229.52, Dexos Gen 3; WSS-M2C961-A1, WSS-M2C963 -A1 OPEL OV0401547- D30, OPEL OV0401547- G30 CHRYSLER MS-11106, FIAT 9.55535-S1 / S3; GM-LL-A-025, GM-LL-B-025; IVECO 18-1811 CLASSE SC1; VW 504.00/507.00

BENEFITS:

- Its special and exclusive formula helps your vehicle maintain maximum horsepower by reducing sludge formation.
- Excellent performance for the higher power and speeds in modern engines.
Enhances life of crankcase.
- The outstanding thermal stability and resistance to oxidation of this oil prevent any degradation, even in extreme usage conditions which helps to extend engine life.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	Visual	Bright & Clear
Color	ASTM D 1500	Neutral
Viscosity @40°C	ASTM D 44	66.93
Viscosity @100°C	ASTM D445	11.39 cSt
Viscosity Index	ASTM D 2270	164.8
Density @15°C	ASTM D 1298	0.850
Pour Point	ASTM 97	-36°C
Flash point	ASTM D 92	237°C
TBN	ASTM D 6304	7.6