



RULEXX PLUS SAE 75W90 API GL-4

DESCRIPTION:

Rulexx Plus SAE 75W90 API GL-4 is a high-performance multigrade, high-pressure gear oil manufactured from high quality mineral base oils and multi-functional extreme pressure additives. It provides excellent low temperature fluidity for safe lubrication during very low temperature transmission and trans axle startup, and also maintains a thick protective oil film during extremely hot operating conditions.

APPLICATION:

SAE 75W90 API GL-4 used in powered transmission and axle drives for cars, highway light and heavy duty trucks, busses, and vans where an API GL-4/GL-5 is required. Rulexx Gear Lubes are recommended for Automotive commercial vehicle's and passenger cars gear type transmission and drive axles operated under high-speed/shock load, high-speed/low torque and low-speed/high-toque conditions.

SPECIFICATIONS:

Rulexx Plus SAE 75W90 API GL-4 Gear oil meets the requirements of all major car manufacturers and the following standards:

API GL-4/GL-5 LS; MIL L 2105 C; FORD WSD-M2C200-C; MACK GO-J Plus; PSA B71 2330

BENEFITS:

- Excellent wet gear performance, shifting and anti-shudder durability.
- Excellent steel-on-steel frictional engagement with good torque transfer capability.
- Maximum equipment life that protects against wear, corrosion, and the formation of harmful deposits.
- Extended drain intervals due to improved oxidation resistance.
- Resistance to oxidation and oil thickening and are compatible to oil seals.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Apperance	VISUAL	LIGHT YELLOW
Kin. Viscosity @ 100°C	ASTM D445	15.51 mm ² /s
Viscosity Index @40°C	ASTM D 2270	105.3
Density @15°C	ASTM D 1298	0.8680
Pour Point	ASTM D97	-38°C
Flash Point	ASTM D 92	-200°C
Antifoam	ASTM D 892	Pass