



RULEXX PLUS BRAKE FLUID TYPE 200 DOT-4

DESCRIPTION:

Rulexx Plus Brake Fluid DOT 4 is an efficient performance nonpetroleum automotive brake fluid, designed for use in conventional hydraulic brakes and clutch systems, where DOT 4 fluids are recommended.

Brake Fluid DOT 4 is a complex mixture of polyglycol ethers, glycol ether borate esters and polyglycols with additional corrosion and oxidation inhibitors. All feature high-quality additives that help deliver outstanding corrosion protection and optimum compatibility with brake system sealing materials.

APPLICATION AND APPROVAL:

Recommended for re-fill or top-up of brake and clutch systems in passenger cars, 4WD's, motorcycles, light and heavy duty commercial vehicles.

- SAE J 1703 / J 1704
- FMVSS 116, DOT 3
- SO 4925 class 3
- CUNA NC 956 DOT 3
- IVECO 18-1820 specifications.

BENEFITS:

- Excellent choice for mixed fleet services.
- Exceptional protection against oxidation, foaming, temperature deposits.
- Highly effective control over shoot, wear and trust.
- Outstanding thermal behaviour at high temperatures.
- Properly balanced dispersancy ensures a clean engine.
- Formulated to provide enhanced fuel economy due to lower viscous drag.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Apperance	VISUAL	VISUAL
Color	ASTM D 1500	LIGHT YELLOW
Kin. Viscosity @ 100°C	D 2270	6.17
Kin. Viscosity @ 40°C	D 2270	14.10
Viscosity Index	D 2270	314.9
Density @15F	D 97	0.8290
pH	FMVSS 116	9.0
Flash Point	ASTM D 92	-200°C
Equilibrium Reflux Boiling Point (ERBP)°C	FMVSS 116	280°C
Wet Equilibrium Reflux Boiling Point (WERBP)°C	FMVSS 116	198°C